

The friendliest gateway seamlessly connects any digital, serial or ethernet-enabled device to the web and any software, system or server you choose.



### Simple Exporting

Exporting data via CSV, Modbus, LonWorks, BACnet, SCADA or DCS and connecting to other systems or supervisors (e.g. Honeywell, Siemens, Trend) is easy.

### Easy to Manage

With [GATEWAY](#), installed on your **Entranet**, viewing data on the dashboards and changing configurations, locally or over the Internet, is simple.

### Modbus

The gateway can function as a TCP/IP Master/Slave and/or RTU Master.

### Rapid Deployment

Deploying your device is quick with plug-and-play inputs and simple web-based setup.

### Tough

The **Entranet**, with its robust ABS case and component potting, is very resistant to physical and chemical damage, and is well suited to harsh environments. IP67 rated.

## CONNECTIVITY

<b>Wireless Connections</b>	GSM/CDMA, GPRS/EDGE. <i>(3G variant only)</i>	
<b>Wired Connections</b>	1x RJ45 Ethernet	
	2x Digital <i>(optional)</i>	
	1x RS232/485 Serial	<i>(option for 2 extra)</i>
<b>Access to Interface</b>	Local	
	Remote	<i>(with siteCONNECT subscription)</i>

## POWER

<b>24V PSU</b>	9 - 32VDC
<b>5V USB Power Adaptor</b>	5VDC

## PHYSICAL

<b>Dimensions (H x W x D)</b>	235.00 x 154.06 x 73.22 mm
<b>Weight</b>	1.1kg
<b>Enclosure Material</b>	Acrylonitrile Butadiene Styrene (ABS)
<b>Enclosure Rating</b>	IP67
<b>Operating Temperature</b>	-20°C to +60°C (-4°F to +140°F)
<b>Thermal Ignition Resistance</b>	HB @ 1.5mm

