

The friendliest gateway seamlessly connects any digital, serial or ethernet-enabled device to the web and any software, system or server you choose.



Seamless Connectivity

Transferring data via CSV, Modbus, LonWorks, BACnet, SCADA or DCS and connecting to other systems or supervisors (e.g. Honeywell, Siemens, Trend) is seamless. 3G connectivity is also available.

Easy to Manage

Viewing data on the **Entranet** dashboards and changing configurations, locally or over the Internet, is simple.

Modbus

The gateway can function as a TCP/IP Master/Slave and/or RTU Master.

Rapid Deployment

Deploying your device is quick with plug-and-play inputs and simple web-based setup.

Industrial-Grade

The **Entranet**, with its robust ABS case and component potting, is very resistant to physical and chemical damage, and is well suited to harsh environments. IP67 rated.

CONNECTIVITY

Wireless Connections	GSM/CDMA, GPRS/EDGE. <i>(3G variant only)</i>
	1x RJ45 Ethernet
Wired Connections	2x Digital <i>(optional)</i>
	1x RS232/485 Serial <i>(option for 2 extra)</i>
Access to Interface	Local
	Remote <i>(with siteCONNECT subscription)</i>

POWER

24V PSU	9 - 32VDC
5V USB Power Adaptor	5VDC

PHYSICAL

Dimensions (H x W x D)	235.00 x 154.06 x 73.22 mm
Weight	1.1kg
Enclosure Material	Acrylonitrile Butadiene Styrene (ABS)
Enclosure Rating	IP67
Operating Temperature	-20°C to +60°C (-4°F to +140°F)
Thermal Ignition Resistance	HB @ 1.5mm

